

CASUN Intelligent Robot GmbH
Suzhou CASUN Intelligent Robot Co., Ltd.

# PRODUCT CATALOG

stock code. 834863

## CASUN Intelligent Robot GmbH Suzhou CASUN Intelligent Robot Co., Ltd.

- © Germany office:Spaldingstr.210, 4.Stock, 20097 Hamburg, Germany Tel: 040 228515982
- O China headquarter: Building 1, Miaoquan Industrial Park, Guli Town, Changshu City, Suzhou City, Jiangsu Province

400-700-6846

**3** +86-512 52868698

vip@casun99.com

www.casun-agv.com



Intelligent logistics project solution Intelligent control system



Mobile robot







# CATALOGUE

ABOUT

Service network

O1 / 06

Company profile /01

Core business /03

/05

Mobile robot

	07 / 54
C1-Latent traction series	/07
C2-Latent lift series	/19
C3-Unit load AGV with conveyor series	/31
C5-Intelligent forklift mobile robot series	/39
CCM-Customization series	/47
CCS-Charging Station Series	/53

1 Intelligent system

55	/ 64
Mobile Robot Control System	/55
Intelligent Warehouse Management System	/57
Intelligent Warehouse Equipment Control System	/59
Intelligent Warehouse Sorting System	/61
Digital simulation system	/63

PROJECT SOLUTION

New energy lithium battery /65

New energy photovoltaic /67

Automobile and parts /69

Flat panel display /71

3C & Semiconductor /73

Logistics and transportation /75

5 Enterprise service

Service Concept /77
Service Item /77
Service Process /78
Follow Us /78

Compatible with 5generation navigation mode Visual navigation + Clusterscheduling

5+ series mobile robot It covers the whole scene of manufacturing and intelligent logistics

Cover all kinds of application 8 series, more than 50 models 16


Founded in 2007 Focus in AGV industries for 16 years


**50**<sup>+</sup>

The business network covers the worldwide 28 subsidiaries, offices and 30+ globalagents

2800<sup>+</sup>

More than 2800 system solutions have been completed and delivered







America o

Mexico

Brazil 0

05 Service Network

South Africa

Serving

The

Globe

0

Russia

Germany

Romania

Chengdu **⊙** India Suzhou nenzhen Philippines Malaysia O Singapore Indonesia

**R&D** centers







Suzhou Shenzhen Shanghai Chengdu



Austrlia 🧿



Xi'an

Service network Headquarter:Suzhou, Shenzhen

Changshu, Wuxi, Nanjing, Changzhou, Hefei, Nantong, Shanghai, Ningbo, Guangzhou, Huizhou, Foshan, Dongguan, Zhuhai, Fuzhou, Wuhan, Zhengzhou, Changsha, Nanchang, Chengdu, Chongqing, Qingdao, Xi 'an, Beijing, Tianjin, Urumqi, Shenyang

Global Agent

USA, Mexico, Brazil, Chile, UK, Ireland, Germany, France, Czech Republic, Ukraine, Romania, Turkey, Malaysia, Singapore, Indonesia, Philippines, South Korea, Japan, Australia, Taiwan, Hong Kong, China...

# **Latent Traction** Series Mobile Robots




Series Introduction Latent traction series mobile robots can lurk under the material truck, use the traction divided into one-way, two-way and omni-directional according to the running direction,



Application Environment









The product performance is stable, and there are a large number of mature application cases;



The car body is flexible and the turning radius is



High cost performance and short delivery period;



Flexible production to ensure smooth production lines;



## Repplication industries and scenarios



Automobiles and parts, new energy lithium batteries, machinery manufacturing, electronics, electrical appliances and other diversified industries;




application scenarios

Transportation of production line materials, raw materials, parts and components, forming a flexible production line, etc.;



#### **Product introduction**

C1-11B one-way latent traction AGV is suitable for workshops with relatively fixed production processes. The working method is that the AGV automatically lurks to the bottom of the material truck after receiving system instructions, and automatically connects to the material vehicle through the AGV traction rod to realize material handling. End-to-end transfer. At present, it has been widely used in the two application scenarios of SPS material supply in automobile assembly workshop and PACK line in new energy lithium battery industry.



Mechanical anti-collision bumper



#### Project case - Automobile assembly workshop project

In the final assembly line and the instrument line, workers stand on the side of the line and operate on the special material truck pulled by the AGV. After completing the current process, they are released to the next station to realize streamlined operation. By replacing the original fixed production line, flexible production is realized, which is also conducive to later expansion and upgrading, and reduces the cost of later line body transformation; through the application of AGV in each link, the entire logistics link is connected in series to realize unmanned Smart delivery.



#### Improve operating efficiency

Realize unmanned handling through AGV, saving warehouse logistics personnel;



#### Improved management efficiency

The AGV system is connected to the production management system, which can remind warehouse personnel to prepare materials in advance, avoid delays in production line, and significantly save personnel management costs



#### Reduce errors

Through automatic material calling, point-to-point material handling is realized, and the error rate due to manual distribution is reduced.













The product performance is stable, and there are a large number of mature application cases;



Short lead time and high Adapt to the lithium cost performance; battery industry and the automobile industry;



Flexible production to ensure smooth production lines;



## Replication industries and scenarios



Diversified industries such as new energy lithium batteries, automobiles and parts, machinery manufacturing, electronics, and electrical appliances.




application scenarios

End-to-end transportation of production line materials, raw materials and parts, forming a flexible production line, etc.

## **Product introduction**

C1-12 one-way latent traction type AGV is suitable for workshops with relatively fixed production processes. end-to-end transfer. A flow production line can also be composed of multiple AGVs to realize flexible production in the factory. At present, it is widely used in the PACK line scene of the new energy lithium battery industry.



#### Project case - Lithium battery PACK line material transfer project

The factory's PACK line material transfer project mainly realizes the material transfer between battery packs from assembly to testing to packaging, and its operation process is a circular assembly line. Through the CRMS mobile robot control system, the system realizes autonomous material calling, intelligent handling, information collection, and intelligent storage, and seamlessly connects with the user's production management system.

Difficulties of the project: This project mainly solves the technical difficulties of docking various peripheral equipment systems, such as transmission equipment, robotic arms, etc.; secondly, it accurately realizes the priority logic judgment of AGV operation, according to the sequence of different stations, the CRMS system automatically selects and determines the most suitable transportation route.

#### **TQCM**

Create a flexible production line and improve the flexibility of production scheduling.



#### Damage reduction

Reduce damage - improve yield rate and accuracy rate: Reduce material damage during handling, and the defective rate is reduced by 90%.




#### Precise location

The transportation accuracy rate is increased to 99%, which meets the peak demand of full production of the whole



#### Intelligent logistics

Realize the optimization of warehouse location, route and task allocation. and the informatization of the whole process.









Adopt advanced SLAM navigation technology;



Adapt to a variety of tooling trucks;



High cost performance and short delivery period;



#### Application industries and scenarios



Diversified industries such as automobiles, auto parts, machinery manufacturing, electronics, electrical appliances, and new energy;




application scenarios

Production line materials, raw materials, parts transportation, flexible production lines, etc.

#### **Product introduction**

C1-14 one-way latent traction AGV is suitable for sites with relatively fixed environmental contours. The navigation mode is SLAM navigation. The working mode is that the AGV automatically lurks to the bottom of the material truck after receiving system instructions, and is automatically hung by the traction bar. Pick-up trucks realize end-to-end transfer. A flow production line can also be composed of multiple AGVs to realize flexible production in the factory. At present, it is mostly used in SPS of automobile assembly workshop.





#### Project case - SPS distribution of small pieces in the final assembly line

Small SPS distribution on the final assembly line, mainly including: interior trim line, final line, chassis line, door line, etc., mainly from the material distribution area, small SPS racks are delivered to the edge of the production line, and then through the upper and lower lines The mechanism is sent to the production line to realize the operation of the SPS material truck along with the production line. It mainly solves the problem of single-set distribution of small materials to the side of the car to run along the line, convenient and fast operation by personnel, space saving in wireless side warehouses, and errors in personnel assembly without errors and missing installations.

#### Improve efficiency

Improve operating efficiency, realize unmanned handling through AGV, and save warehouse logistics personnel;



#### Space saving

Save storage space at the edge of the production line, and assist customers in realizing 5S management at the edge of the



#### Reduce errors

Through automatic material calling, point-to-point material handling is realized, and the error rate due to manual distribution is











The product performance is stable, and there are a large number of mature application cases;

The car body is flexible and the turning radius is

High cost performance and short delivery period;



Flexible production to ensure smooth production lines;

#### Application industries and scenarios



Diversified industries such as new energy lithium batteries, automobiles and parts, machinery manufacturing, electronics, and electrical appliances.




application scenarios

Production line materials, raw materials, parts transportation, flexible production lines, etc.



#### **Product introduction**

C1-22 two-way latent traction AGV is suitable for workshops with relatively fixed production processes. The working method is that the AGV automatically lurks to the bottom of the material truck after receiving system instructions, and automatically mounts the material vehicle through the traction rod to realize end-to-end terminal transport. A flow production line can also be composed of multiple AGVs to realize flexible production in the factory. At present, it has been widely used in the automobile and parts industry, new energy lithium battery industry, etc.





#### Project case - Auto parts project

Through the two-way AGV, at the site with narrow passages, by switching directions, the exchange of empty and full material trucks can be realized, and the material transfer of raw materials such as exhaust pipes and seats can be realized through special material vehicles, reducing the Materials are piled up at the edge of the production line, rational use of warehouse space, placement of empty and full parts, and increase the number of placements.



#### Improve efficiency

Improve operation efficiency, realize unmanned handling through AGV, and save warehouse logistics personnel;



#### Space saving

Saving storage space on the production line, assisting customers to realize 5S management on the line;



#### Automatic material call

Through automatic material call, point-to-point material handling can be realized, and the error rate due to manual distribution can be reduced.












C1-24 bidirectional latent traction AGV adopts SLAM navigation or QR code navigation. The working mode is that the AGV automatically lurk to the bottom of the trolley after receiving the system instruction, and automatically hooks the trolley through the traction bar to achieve end-to-end transfer. It can also be composed of multiple AGVs to form a flow production line to achieve flexible production in the factory. At present, it has been widely used in new energy photovoltaic, automobile and parts industry, new energy lithium battery industry.









#### **Product advantages**



Adopt advanced SLAM navigation technology;

Adapt to a variety of tooling trucks;

High cost performance and short delivery period;


## Application industries and scenarios

#### **application industry**

Diversified industries such as automobiles, auto parts, machinery manufacturing, electronics, electrical appliances, and new energy;

application scenarios

Production line materials, raw materials, parts transportation, flexible production lines, etc.



## Latent **Lift Mobile Robot**



Series

introduction into one-way, two-way and omni-directional



Application environment

	Model	C2-22B	C2-23B	C2-26B	C2-36	C2-37
						GRUT STORY
	Dimension	L940*W650*H253 (mm)	L1180*W860*H300 (mm)	L1600*W860*H350 (mm)	1540*920*370(mm)	L2000*W1000*H840(mm)
	Max Load Capacity	1000kg	1500kg	1500kg	1500kg	1000kg / 1500kg / 2500kg
Par	Weight	150kg	400kg	400kg	410kg	630kg
Basic Parameters	Rotation Diameter	1087mm	1180mm	1770mm	1740mm	2227mm
ers	Relative Rotation	Yes	Yes	NO	NO	NO
	Size of Lifting Platform	860*600mm	1050*735mm	1280*800mm	1276*796mm	1464*588(mm)
	Max Lifting Distance	60mm	50mm	60mm	60mm	248mm
- Service V	Navigation Mode	QR/SLAM	QR/SLAM	QR	QR/SLAM	QR/SLAM
Navi	Navigation Accuracy	±10mm / ±15mm	±10mm/±15mm	±10mm	±10mm/±15mm	±10mm /±15mm
Navigation Performance	Stop Accuracy	±5mm / ±10mm	±5mm/±10mm	±10mm	±5mm/±10mm	±5mm / ±10mm
e -	Stop Angle Accuracy	±1°	±1°	±1°	±1	±1°
2	Moving Direction	Forward,Backward,Rotate	Forward, Backward, Rotate	Forward,Backward,Rotate	Forward, backward, sideways, rotating	Forward, backward, sideways, rotating
Pex	Drive Mode	Two-wheel rudder drive	Two-wheel rudder drive	Two-wheel rudder drive	Two-wheel rudder drive	Steering wheel drive
Movement Performance	Accelerated Speed	0.5m/s <sup>2</sup>	0.35m/s²	0.35m/s <sup>2</sup>	0.5m//s <sup>2</sup>	0.5m/s <sup>2</sup>
ent	Max Moving Speed	2m/s	1.2m/s	1.0m/s	1m/s	60m/min
	Max Climbing Capacity	≤3°	≤3°	≤3°	≤3°	≤3°
-	Battery	Lithium battery	Lithium battery	Lithium battery	Lithium iron phosphate battery	Lithium battery
Ba Perfo	Charging Mode	Collision charging	Collision charging	Side charging	Side charging / ground charging	Side charging/ground charging
Battery erformance	Charging time	Charge time ≤1H after complete discharge	Charge time ≤1H after complete discharge	Charge time ≤1H after complete discharge	Charge time ≤1H after complete discharge	Charge time ≤1H after complete discharge
ce	Rated Duration	4H	6H	6Н	4H	6Н
Network	Communication	WiFi/5G	WiFi / 5G	WiFi/5G	WiFi/5G	WiFi / 5G
-	Security Alarm	- Light warning - Voice broadcast	- Light warning - Voice broadcast	- Light warning - Voice broadcast	- Light warning - Voice broadcast	- Light warning - Voice broadcast
Perfu	Security Sensing Range	≤3m adjustable	≤3m adjustable	≤3m adjustable	≤3m adjustable	≤3m adjustable
Protective Performance	Safety Protection	-Front obstacle detection sensor -Mechanical anti-collision mechanism -Emergency stop switch	-Front and rear obstacle detection sensors - Mechanical anti-collision mechanism - Emergency stop switch	-Front and rear obstacle detection sensors - Mechanical anti-collision mechanism - Emergency stop switch	- Diagonal obstacle sensor, - Mechanical anti-collision mechanism - emergency stop switch	-Front and rear diagonal obstacle detection sensors -Mechanical anti-collision mechanism -Emergency stop switch





The body height is smaller, suitable for lower space operation;

It can be used as a flexible production line to ensure smooth production;

Composite navigation can be used, and the docking accuracy is high; With the function of relative rotation, the flexibility is higher;

#### Application industries and scenarios

application industry

Diversified industries such as photovoltaics, automobiles and parts, logistics and distribution, electronics, and electrical appliances.

application scenarios

 $Goods-to-person\ selection, production\ line\ raw\ materials,$ end-to-end transportation of parts and components, forming a flexible production line, etc.



#### **Product introduction**

C2-22B is a latent lifting AGV. It uses trackless navigation and can change the route according to on-site production changes. The model is small and compact, and the load can reach 1000KG after upgrading. The body and the lift plate can be rotated relative to each other. Working method: After the AGV receives the system command, the AGV lurks to the bottom of the material rack, lifts the material rack up, and carries out material transportation; it can also be composed of multiple AGVs to form a mobile production line to achieve flexible production. It has been widely used in automobiles and spare parts Parts industry, photovoltaic industry, 3C and semiconductor industries.





#### Project case - Automobile back door assembly workshop project

Through the two-way mobile robot, at the site with narrow passages, the exchange of empty and full material trucks can be realized by switching directions, and the material transfer of raw materials such as exhaust pipes and seats can be realized through special material trucks, reducing Reduce the accumulation of materials at the edge of the production line, rationally use the warehouse space, place empty and full materials, and increase the number of placements.



#### Flexible production

Flexible production line, the rate of on-site change is increased, and the incompatibility of the production line caused by changes in production orders is reduced.



**TQCM** 

Reduce the number of loading and unloading operators and reduce personnel fatigue.



Strong reliability

Production can still be carried out if a single equipment fails, and the risk of the entire line stopping due to equipment failure at the station is improved.







C2-23B performs precise positioning according to dispatching tasks, and independently completes a series of operations of lifting, transportation, and unloading. It can choose material sorting system, platform, and body relative rotation configuration, etc. This series is divided into one-way, two-way and omni-directional according to the running direction of the mobile robot. The navigation method can choose QR code navigation and SLAM navigation, and the load capacity can reach 1500kg. At present, it has been widely used in many industries such as new energy photovoltaics, automobiles and parts, logistics and distribution, food and beverage, 3C and semiconductors, and household appliances.





#### **Product advantages**



The product performance is stable, and there are a large number of mature application cases;

The car body is flexible and the turning radius is small:

High delivery timeliness and high cost performance;

Flexible production to ensure smooth production lines;



#### Application industries and scenarios



New energy photovoltaics, automobiles and parts, logistics and distribution, electronics and electrical, medical and other industries.



application scenarios

Production line materials, raw materials, parts transportation, goods-to-person selection, flexible production lines, etc.



#### Project case - Cargo sorting project in a finished tobacco warehouse workshop

This project is mainly used in the storage and sorting process of finished products in the tobacco industry. It mainly uses mobile robots to realize automatic handling and manipulator docking to realize automatic storage and sorting work; through the use of mobile robots, a certain tobacco logistics greatly It reduces the number of personnel and labor intensity, and replaces manual labor for tedious and repetitive warehousing and warehousing actions.

In addition, the mobile robot is automatically docked with various process production equipment, which connects the production of the prprocess links in series and realizes factory automation.

#### Improve efficiency

Flexible production line, the rate of on-site change is increased, and the incompatibility of the production line caused by changes in production orders is reduced.



#### Increase capacity

Seamlessly connect with WMS system, realize optimization of storage location, route, and task allocation, rationally plan warehouse lavout, maximize use of space, and increase warehouse location by 20%.



#### Intelligent Scheduling

The storage information data of the warehouse location, inbound and outbound tasks, and on-site inbound and outbound equipment (mechanical arms, stacking machines, manual warehousing operation terminals, etc.) are managed by the customer's WMS system to monitor the status of factory materials in real time.



#### Cost saving

Reduce the number of operations by personnel, reduce the intensity of manual labor, reduce the rate of operational errors. improve the flexible process, and save a lot of labor costs.











The product performance is stable, and there are a large number of mature application cases;



Adapt to the lithium battery industry, tailor-made;



Flexible production to ensure smooth production lines;



#### Application industries and scenarios



Diversified industries such as new energy lithium batteries, automobiles, auto parts, and machinery manufacturing.




application scenarios

End-to-end transportation of production line materials, raw materials and parts, forming a flexible production line, etc.



#### **Product introduction**

C2-26B two-way latent lifting mobile robot is suitable for workshops with relatively fixed production processes. The working method is: the mobile robot automatically lurks to the bottom of the material truck after receiving system instructions, and docks with the material vehicle through the lifting platform. Realize end-to-end transfer. A mobile production line can also be composed of multiple mobile robots to achieve flexible production in the factory. At present, the most widely used is the





#### Project case - Lithium battery PACK line project

The factory PACK line transfer project mainly realizes the material transfer between battery packs from assembly to testing to packaging, and its operation process is a circular assembly line. Through the CRMS mobile robot control system, autonomous ordering of materials, intelligent handling, information collection, and intelligent storage are realized, and it is seamlessly connected with the user's production management system.

Difficulties of the project: This project mainly solves the technical difficulties in the docking of various peripheral equipment systems, such as transmission equipment, robotic arms, etc.; secondly, it accurately realizes the priority logic judgment of the operation of the mobile robot, according to the sequence of different stations In order, the CRMS system automatically selects and determines the most suitable transportation route.

## Reduce costs

Reduce the investment cost of fixed equipment: create a flexible production line and improve the flexibility of

production scheduling.



#### High reliability

Improve yield rate and accuracy rate: reduce material damage during handling, and reduce defect rate by 90%.



#### Precise positioning


Improve the positioning accuracy of transportation: the transportation accuracy rate is increased to 99%, which can meet the peak



#### Intelligent logistics

Realize intelligent logistics in the field: realize the optimization of warehouse location, route and task allocation, and informatization of the









The product performance is stable, and there are a large number of mature application cases;



Omni-directional operation, 360degree safety protection;



Flexible production, which can be adapted to battery packs of various specifications.



#### Application industries and scenarios



application industry

New energy lithium batteries, automobiles, auto parts, machinery manufacturing and other diversified industries;




application scenarios

PACK line, raw materials of production line, end-to-end transportation of parts and components, forming a flexible production line, etc.



#### **Product introduction**

C2-36 is a latent lifting AGV, equipped with omnidirectional drive, using QR code navigation, and the load can reach 1500KG. The model is compact and the lifting stroke is 60mm. Working method: After the AGV receives the system command, the AGV lurks to the bottom of the material rack, lifts the material rack, and carries out material transportation; it can also be composed of multiple AGVs to form a mobile production line to achieve flexible production. It has been widely used in new energy lithium batteries., automobile and parts industry, photovoltaic industry, 3C and semiconductor industry.





#### Project case - Lithium battery PACK line project

 $It \ mainly \ realizes \ the \ product \ transfer \ between \ battery \ packs \ from \ assembly \ to \ testing \ to \ packaging, \ and \ its \ operation \ process \ is \ a$ circular flexible production line. Through the system, autonomous ordering of materials, intelligent handling, information collection, and intelligent storage are realized, and it is seamlessly connected with the user's production management system.

(2) Difficulties of the project: This project mainly solves the function of the AGV carrying the PACK material car to realize the lateral movement, reduces the space of the PACK material car running channel, and at the same time ensures that the orientation of the PACK material car is consistent with the site; secondly, it solves the problem Explain the technical difficulties of docking various peripheral equipment systems: such as MES docking of manual stations, test equipment, manipulators, safety grating docking of automatic stations, etc.



#### Cost reduction

Reduce the investment cost of fixed equipment: create a flexible production line and improve the flexibility of production scheduling.



#### High reliability

Improve the health rate and accuracy rate, reduce material damage during the handling process, and reduce the unhealthy rate



#### Precise positioning

Improve the positioning accuracy of transportation, and the transportation accuracy rate is increased to 99%, which meets the peak demand of full production of the whole line;



#### Intelligent logistics


Realize intelligent on-site logistics: Realize optimization of warehouse locations, routes, and task allocation, and informatization of the entire







performs precise positioning according to the scheduling task, and independently completes a series of operations of lifting, t ransporting and unloading. The navigation method is SLAM navigation, the load capacity is compatible with 1T, the lifting hei ght is up to 248mm, and it can be applied to various height positions; it can detect low obstacles, and can perform two safety protections while lifting, which has a price competitive advantage.





#### **Product advantages**



The lifting stroke can reach 248mm, which can be applied to various hei ghts of work stations.



Omni-directional operation, 360degree safety protection.



Flexible production, which can b e adapted to battery packs of var ious specifications.



#### Application industries and scenarios



New energy lithium batteries, automobiles, auto parts, mac hinery manufacturing and other diversified industries;



#### application scenarios

PACK line, raw materials of production line, end-toend transportation of parts and components, forming a fl exible production line, etc.



#### Project case - Lithium battery PACK line project

It mainly realizes the material transferring between battery packs from assembly to testing to packaging, and its operation process i s a circular assembly line. Through the CRMS mobile robot control system, the system realizes autonomous material calling, intellige nt handling, information collection, and intelligent storage, and seamlessly connects with the user's production management syste m. The project uses AGV as a flexible distribution unit, which effectively solves the transportation problem compatible with hundred s of products of different models and specifications.

Difficulties of the project: This project mainly solves the function of the AGV carrying the PACK trolley to realize the lateral movemen t, reduces the space of the PACK material car running channel, and at the same time ensures that the orientation of the PACK trolley i s consistent with the site; secondly, it solves the problem explained the technical difficulties of docking various peripheral equipme nt systems: such as MES docking of manual stations, test equipment, manipulators, safety grating docking of automatic stations, etc



#### **TQCM**

Create a flexible production lin e and improve the flexibility of production scheduling



## Reduce damage

Improve yield rate and accu racy rate: reduce material d amage during handling, an d reduce defect rate by 90%



#### Intelligent logistics

Realize the intelligentizatio n of onsite logistics, realize t he optimization of warehou se location, route and task a llocation, and informatizati on of the whole process;



#### Digitalization &visualization

Accurately collect data such as material efficiency, frequ ency, utilization rate, etc., a nd analyze them to improve the process and increase e fficiency.





- Mechanical Anti-collision Structure; - Mechanical Anti-collision Structure;

-Emergency Stop Switch

-Emergency Stop Switch

# Load and transferring mobile robot




Series

introduction choose QR code navigation, laser positioning navigation, and SLAM navigation.




Application environment




	Model	C3-01	C3-04	C3-05
		COLD TO THE PARTY OF THE PARTY	Contra	COSED
	Dimension	L940*W680*H755 (mm)	L1550*W950*H2150 (mm)	L1550*W950*H1500 (mm)
	Max loading capacity	100kg	300kg	300kg
ъ.	Vehicle weight	300kg	350kg	300kg
Basic	Rotation diameter	1250mm	1725mm	1725mm
Basic Parameters	Docking height	820mm	the lower layer is 450mm the upper layer is 1300mm	the lower layer is 450mm the upper layer is 1000mm
S .	Material supporting size	700*450mm	/	/
•	Docking direction	Forward,Backward	backward	backward
-	Material transfer mode	Roller	belt	belt
_	Navigation mode	QR/SLAM	SLAM	SLAM
Navi	navigation accuracy	±10mm /±15mm	±10mm	±10mm
Navigation Performance	Stop accuracy	±5mm / ±10mm	±5mm	±5mm
Ce n	Stop Angle accuracy	±1°	±1°	±1°
	Traveling direction	Forward,Backward,Rotate	Forward, backward, rotate	Forward, backward, rotate
Pel M	Drive mode	Two-wheel differential drive	Two-wheel differential drive	Two-wheel differential drive
Movement Performance	Acceleration	0.5m/s <sup>2</sup>	0.3m/s <sup>2</sup>	0.3m/s <sup>2</sup>
nent	Max running speed	1.5m/s	1.2m/s	1.2m/s
	Maximum climbing capacity	≤3°	≤3°	≤3°
_	Battery type	Lithium battery	Lithium battery	Lithium battery
Ba	Charging mode	Side charging	Side charging	Side charging
Battery Performance	Charging time	Charge time after full discharge: side charge ≤1H	Charge time after full discharge: side charge ≤1H	Charge time after full discharge: side charge ≤1H
ice -	Rated endurance	4H	8H	8H
Network	Communciation mode	WiFi/5G	WiFi/5G	WiFi/5G
77.5	Safety warning	- Light warning - Voice broadcast	- Light warning - Voice broadcast	- Light warning - Voice broadcast
Pro	Safe sensing range	≤3m adjustable	≤3m adjustable	≤3m adjustable
Protective Performance	Safety protection	-Front obstacle detection sensor -Mechanical anti-collision	- Front and rear diagonal obstacle	-Front and rear diagonal obstacle detection sensor 360° laser obstacle avoidance
	5.	mechanism	- Machanical Anti-collision Structure	-Machanical Anti-collision Structur

-Emergency stop switch



C3-01 is a roller-carrying mobile robot, which can use QR code navigation, laser positioning navigation, and SLAM navigation technology. Load capacity is 100kg. Double-layer workstations can realize fast interaction between empty and full materials. It can be widely used in new energy lithium battery, new energy photovoltaic, injection molding industry, 3C and semiconductor, flat panel display and other industries.





#### **Product advantages**



Adopt the most advanced SLAM navigation technology;



It adopts double-layer drum design, matching with the double-layer drum line of the injection molding machine, and automatically completes the empty and full exchange;



The car body is flexible and the turning radius is small; it cooperates with the injection molding machine to realize the unmanned operation of the process;



## Replication industries and scenarios

application industry

New energy lithium battery, injection molding industry, 3C and semiconductor, LCD panel and other industries.



application scenarios

The process scene where the material of the material box type is docked by the roller



#### Project case - 3C injection molding workshop project

19 injection molding machines transfer the injection molded parts between 4 assembly machines; through the CRMS mobile robot control system, autonomous ordering, intelligent handling, information collection, and intelligent storage are realized, and there is no connection with the user's production management system. Seam docking, unmanned operation throughout the process.

Difficulties of the project: This project mainly solves the technical difficulties in the docking of various peripheral equipment system s, such as transmission equipment, robotic arms, etc.; secondly, it accurately realizes the priority logic judgment of the operation of the mobile robot, according to the sequence of different stations In order, the CRMS system automatically selects and determines th e most suitable transportation route.



Realize unmanned

Build a black lamp factory,

dock with injection moldi

ng machine robots and co

nveyor lines, and realize u

nmanned chemical factori

## Data interaction and sharing

Interaction with Party A's equipme nt and systems: CRMS system can be seamlessly connected with onsite automation equipment syste ms and customer systems to realiz e data transmission.



#### Intelligent logistics

Warehouse location storage information data, inboun d and outbound tasks, and onsite inbound and outbo und equipment (mechanical arms, stacking machines, manual warehousing operation terminals, etc.) are m anaged by the customer's WMS system to monitor the status of factory materials in real time.















C3-04, mainly used in photovoltaic industry cell production workshop, the basket automatic loading and unloading. The navigation mode is SLAM navigation, the load capacity is 300kg, and the maximum speed is 1.2m/s. The working mode is that  $after \, receiving \, the \, system \, instruction, \, the \, AGV \, can \, automatically \, dock \, and \, transport \, the \, basket. \, The \, AGV \, basket \, structure$ designing has reserved the configuration space of wet basket operation, and can be designed and developed according to the technical requirements of wet basket (acid, alkali and pollution prevention).











#### **Product advantages**



Using advanced SLAM+ visual navigation technology;



Double-layer and double-track transmission, which can improve production efficiency;

Adopt type structure, 360° obstacle avoidance, and ensure production

#### Application industries and scenarios

#### **application industry**

Photovoltaic industry, 3C and semiconductor, LCD panel and other industries.




application scenarios


Process scenario of automatic loading and unloading and box type materials docking through the conveyor line








C3-05, is mainly used for photovoltaic industry cell production workshop, BIN box automatic loading and unloading. The navigation mode is SLAM+ visual navigation, the loading capacity is 300kg, and the maximum speed is 1.2m/s. After receiving the system instruction, the AGV automatically interconnects and transports the BIN box.













Using advanced SLAM+ visual navigation technology;

Double-layer and double-track transmission, which improve production efficiency;

Adopt type structure, 360° obstacle avoidance, and ensure production

## Application industries and scenarios

#### application industry

Photovoltaic industry, 3C and semiconductor, LCD panel and other industries.

application scenarios

BIN box automatic loading and unloading process scenarios. Bin type Materials are docking through transport cables



## — Intelligent forklift mobile robot



Intelligent forklift series mobile robots are divided into handling type and stacki introduction mobiles and parts, flat panel displays, food and beverage, 3C and semiconducto



Application environment





suitable for workshops with limited factory area and multiple pr oduction processes. The working method is that the AGV autom atically picks up the bottom of the pallet after receiving the syst em command, and realizes end-to-





#### **Product advantages**



The car body is small and exquisite, and can be carried in narrow passages;



When the turning radius is limited, it can tur n 90 degrees and turn around 180 degrees i



The minimum rightangle stacking channel wi dth is 2m



#### Application industries and scenarios



Diversified industries such as new energy lithium batteries, automobiles and parts, machinery manufacturing, electroni cs, electrical appliances, and new energy.



application scenarios

Production line raw materials, parts transportation, etc.



Laser navigation sensor

Mechanical anti-collision strip

#### Project case - Automobile air pipe production workshop and finished product warehousing project

Project features: Break through the barriers of information transmission, by connecting to the customer's ERP system, reading the feedback i nformation of the line scanning code, according to the type of material, the intelligent dispatching robot will send the goods to the inspecti onfree station and dock with the outdoor mobile robot, seamless relay. Or send it to the GP12 waiting area for manual sorting, and integrate the indoor and outdoor material transportation into one, realizing the unmanned transportation of materials across the factory from the pro duction line to the outdoor warehouse.

Project features: Break through the barriers of information transmission, by connecting to the customer's ERP system, reading the feedback i nformation of the line scanning code, according to the type of material, the intelligent dispatching robot will send the goods to the inspecti onfree station and dock with the outdoor mobile robot, seamless relay. Or send it to the GP12 waiting area for manual sorting, and integrate the indoor and outdoor material transportation into one, realizing the unmanned transportation of materials across the factory from the pro duction line to the outdoor warehouse.

#### Improve efficiency

Improve the efficiency and accura cy of lineside transportation, so t hat materials can be accurately de livered to the corresponding buff



#### High reliability

Improve the yield rate and accuracy rate: reduce material damage durin g handling, and increase the accura cy rate to 99%



#### Cross-factory transportation

The efficiency of crossfactory transshipment is im proved, and the indoor arrival information can be transmitted to the outdoor mobile robot for conn ection at the first time, without waiting time wast







C5-B6 carries out precise positioning according to dispatching tasks, and independently completes a series of operations of lifting, transportation, and unloading. The navigation method is SLAM navigation + two-dimensional code assisted positioning, with a load capacity of 500Kg and a lifting stroke of 120mm. Available In new energy lithium batteries, automobiles and parts, flat panel display, food and beverage, 3C and semiconductor industries.





#### **Product advantages**



The car body is flexible and can rotate 3



The appearance is compact and can be appli ed in scenarios with small logistics channels



High delivery time and hi gh cost performance



#### Application industries and scenarios

application industry

Auto parts industry, 3C and semiconductor industry



application scenarios

Applicable to the handling scene of small trucks



#### Project case - Auto parts project

This project uses C5-B6 intelligent for klift trucks to realize the distribution of raw materials from the warehouse of raw materials to the manual realized from the contraction of tstation of the production line, and the material distribution of small racks. Area, to meet the on-site narrow roadway transportation; realize the scene operation of material transportation. Realize intelligent planning of the optimal path: Relying on the AI algorithm, the AGV can independently judge the priority of the transportation task and formulate the optimal path.



**TQCM** 

Cost reduction and effici

ency increasereplace ma

nual handling and logist

ics distribution, reduce I

abor input and improve

production efficiency;





It can realize the problem of small rack handling, an d it can realize rack handli ng in the environment wit h small space area;



## Accurate positioning

Improve the positioning accuracy of transportation: the transportation a ccuracy rate is increased to 99%, whi ch meets the peak demand of full pr oduction of the whole line;



#### Intelligent logistics

Realize the intelligentization of logi stics in the factory: realize the intera ction of multisystem docking inform ation and the informatization of the whole process.









Manual/

automatic switch



#### **Product advantages**



Stable product performance and high navigation accuracy;

<u>ල</u> The body design is compact, and the turning radius is only 1350mm, which is suitable for logistics handling in narrow

lanes of various industries;

Flexible production to ensure smooth production lines; Flexible production to ensure smooth production

0

### Application industries and scenarios




New energy lithium battery, 3C electronics, food, military industry, traditional manufacturing and other diversified enterprises.



Production line pallet material raw materials, parts end - storage ground/low shelf - multi-specification Chuan-shaped pallet handling on the side of the production line.

## **Product introduction**

: C5-D1 mini stacking laser forklift has a load capacity of 1000KG, a running speed of up to 1.2m/s, and a lifting height of 1.6m; the extreme dimensions L1653\*W856\*H2295mm make it capable of The ability to operate in extremely narrow lanes requires a minimum width of 900mm for logistics channels (1200mm for ordinary forklifts), which greatly improves space utilization. At present, it has been widely used in diversified enterprises such as new energy lithium batteries, logistics and circulation, 3C and semiconductors, food and beverage, and traditional manufacturing









Laser navigation sensor



Mechanical anti-collision strip

Status Light



#### Project case - A lithium battery module product inbound and outbound transportation project

This project uses a C5-D1 intelligent forklift to automatically transport battery module products into and out of the warehouse. It can be also shown to be a considered from the constant of the constant olift up to 1.6m and meet the on-site narrow roadway transportation.

## Reduce costs

reduce equipment and manpower input costs;



#### High reliability

improve the timeliness of material transportation, and the transportation accuracy rate is increased to 99%, which can meet the peak demand of full production of the whole line;



#### High safety

improves the safety of product transportation and ensures the product yield;



#### Logistics intelligence

realizes the intelligentization and automation of the entire production process, monitoring and tracking of the whole process from product offline storage - delivery, production data statistics, and report generation.



# GGM

哈

Series introduction

customized and developed according to the actual needs of the new energy lithium battery project, with flexible applications. At present, special-purpose robots for new energy include: double-fork lifting mobile robots, single-fork lifting mobile robots and single-cantilever mobile robots, which are mainly used to complete the handling and loading and unloading of pole coils, which can meet the high-precision docking of the lithium battery industry. MES system docking, multiple safety protection, production requirements for strict environmental cleanliness.



Application environment  $-10^{\circ}\text{C} \sim 45^{\circ}\text{C}$ ; no dust, flammable, explosive and corrosive gases.



#### 产品型号

#### CCM-51 Double fork lifting AGV

#### CCM-52 Single fork lifting AGV





Ва	Dimensions	L1800*W1800*H1800(mm)	L1800*W1500*H1200mm
sic Par	Maximum Load	1800kg	1800kg
Basic Parameters	Rotation Diameter	2435mm	2220mm
ers	Docking Height	1800±50mm	1300~1800mm
	Navigation Method	Laser Slam/QR code	Laser Slam/QR code
Navigation Performance	Navigation Accuracy	±10mm	±10mm
Navigation erformance	Stop Accuracy	±5mm	±3mm
ο -	Docking Accuracy	±1mm	±2mm
Pe	Moving Direction	Forward, Backward, Turn, Rotate, Transverse Moving	Forward, Backward, Turn, Rotate, Transverse Moving
Athletic Performance	Drive Mode	teering Wheel Drive	teering Wheel Drive
ic	Maximum Moving Speed	1.0 m/s	1.0 m/s
	BatteryType	Lithium Battery	Lithium Battery
Ba Perfo	Charging Method	Side Charging	Side Charging
Battery Performance	Charging Time	≤1.5H After Full Discharge	≤1H After Full Discharge
се	Rated Endurance	6H	6H
Network Performance	Communication Method	WiFi / 5G	WiFi / 5G
	Safety Alert	Light Warning; Voice Broadcast	Light Warning; Voice Broadcast
ъ_	Safety Sensing Range	Adjustable when ≤3m	Adjustable when ≤3m
Protection Performance	Security	5 Obstacle Detection Sensors; Mechanical Anti-collision Structure; Emergency Stop Switch	4 Obstacle Detection Sensors; Mechanical Anti-collision Structure; Emergency Stop Switch






CCM-51 is a double-fork lifting AGV. Its working mode is: one pair of forks are placed with a full roll of material, and the other pair of forks are placed with an empty reel. The two states are operated alternately at the same interface to realize automatic loading and unloading of materials.


At present, the most widely used in the new energy lithium industry cell production workshop of the front section of the process, for foil and uncut pole roll handling.




#### **Material Specification**










Drum	Drum inner diameter	Drum outer diameter	Drum length	Drum diameter	Weight
Empty drum	152mm	212mm	1100mm	1	/
Full drum	152mm	212mm	1100mm	≤1200mm	≤1800KG







The navigation mode is optional: SLAM navigation or QR code navigation;

Automatic docking with the line equipment to realize the process of unmanned operation;

Double fork design is adopted to complete the empty and full exchange, improve work efficiency and reduce the waiting time of equipment downtime;

High precision control, the docking accuracy with the equipment is ±1mm.

#### Application industries and scenarios

New energy lithium industry; Coil material transport in cell workshop






CCM-52 is a single-fork lifting AGV. Its working mode is as follows: the AGV carries a full roll of material or an empty reel for automatic docking with the connection port to realize automatic loading and unloading of materials.


At present, the most widely used in the new energy lithium industry cell production workshop of the front section of the process, for foil and uncut pole roll handling.




#### **Material Specification**









Drum	Drum inner diameter	Drum outer diameter	Drum length	Drum diameter	Weight
Suitable coiling	152mm	200mm	1100mm	≤1200mm	≤1800KG





The navigation mode is optional: SLAM navigation or QR code navigation;


Automatic docking with the line equipment to realize the process

of unmanned operation;

High precision control, the docking accuracy with the equipment is ±2mm.

#### Application industries and scenarios

New energy lithium industry; Coil material transport in cell workshop



# Charging Station Series



	00
Charging mode	side charge
Model	CCS-11
Dimension	L600xW380xH1000(mm)
Voltage	Power
24V	1500W-5000W
48V	1500W-5000W



Charging mode	side charge
Model	CCS-12
Dimension	L669*W488*H1018(mm)
Voltage	Power
24V	4000W-6000W
48V	2500W—6000W

## ■ 系列介绍

CCS charging station series, composed of charger, control unit, display unit, telescopic electrode, etc., with voltage and current over voltage overload protection mechanism, charging speed, high safety performance. This series is divided into: side charge, ground charge, impact charge, wireless charge,



Charging mode	ground charge
Model	CCS-21
Dimension	L600xW380xH1000(mm)
Voltage	Power
24V	1500W-5000W
48V	1500W-5000W



Charging mode	impact charge
Model	CCS-31
Dimension	L490*W385*H355(mm)
Voltage	Power
24V	1500W—5000W
48V	1500W—5000W






The mobile robot control system mainly deals with the task assignment, path planning, traffic control and state monitoring of robot cluster, and completes data collection through the sensing module carried by mobile robot, so as to analyze and make decisions on production efficiency. At the same time, it provides open standard API, which is easy for customers' business systems to develop and call and provides a solid guarantee for customers to introduce large-scale mobile robots in intelligent warehousing and intelligent factory scenarios.



#### **System Structure**





support the coexistence of combined traffic control with other AGV manufacturers and multiple navigation modes

Multi-effect compatibility

Provide standard interface for customized development and support docking with elevators, elevators and other customer automation equipment

#### Standard interface

#### Cluster scheduling

Large-scale cluster scheduling of 1000+ robots can be realized

#### Bs architecture

configure and maintain the system through the browser

**CRMS** 

CASUN Robot Management System

#### Multi-scene collaboration


cross-floor and cross-regional collaborative scheduling is supported

#### Rapid deployment

low-code drag-and-drop process drawing, rapid software deployment, friendly man-machine interface, simple operation and easy to use.



## System Interface




Elevator Configuration Interface

Map Editing Interface





# **System Structure**






support TCP, WebAPI, WebService and other data interaction protocols, seamlessly connect with the upper MES/ERP and other systems







#### System Interface



Permission management interface


storage management interface





Intelligent storage equipment control system is a management control system connecting WMS and intelligent hardware (AGV, conveyor, RFID equipment, etc.). The tasks of the upper layer are decomposed into dispatching instructions and sent to each automatic equipment. Meanwhile, the warehouse operating environment and equipment running status are monitored, and equipment abnormalities are timely warned. Finally, the unified monitoring and scheduling of various automatic equipment in storage is realized, and the automation efficiency is improved.



















Intelligent warehouse sorting system is a comprehensive solution system for intelligent logistics sorting scenarios. The system combines the AGV control function of management, WCS, WMS basic function, at the same time in intelligent sorting scene have special sorting control system of AGV data through WCS system and WMS data after fusion depth, the prediction of the task and sequence of sorting and evaluation and reasonable dispatching sorting task, implement efficient sorting. It is especially suitable for express e-commerce, warehousing and distribution centers or transport centers in logistics and circulation industry





#### **System Structure**











Casun's digital simulation system can achieve 1:1 simulation of robots. It can not only realize synchronous simulation of robots in real scenes through digital twin technology, but also complete validity verification of the scheme and assist project decision-making through simulation tools of the system in the scheme design stage



#### Multi-scene application

fine-grained simulation control parameters can adapt to the simulation requirements of various scenarios

Rich simulation — configuration tools


Support 2D and 3D simulation

#### Real-time data transmission

efficient and timely data collection, transmission and analysis, and decision support for the status and expectation of production and operation



#### **System Structure**





#### System Interface



CASUN Digital Simulation System



# **NEW ENERGY LITHIUM BATTERY**

# Requirement points

trend, and the industry innovation is accelerating. At the same time, lithium battery manufacturing process from automation to intelligent high-speed transformation. Industrial mobile robot AGV/AMR has been introduced on a large scale to replace the traditional process in the front, middle and rear stages of the process, improve the flexibility and efficiency of the production line, stabilize the quality and delivery time, and form a data closed loop for process tracking.

## Industry trends

Industry

Overview

New energy vehicles, low carbon environmental protection requirements and energy crisis push up the development progress of lithium electric industry



The policies for Industry investment and financing are loose, and leading enterprises lead the expansion and expansion strategy



The popularization of the concept of de-artificialization in logistics operation links and the strong demand for flexible manufacturing



The mature application of mobile robots in the early, middle and late stages promotes the development of industry standardization
























# Smart logistics solution

Improve space utilization rate

the space is small, and the introduction of AGV/AMR flexible line can replace the traditional large conveying line

Flexibility

AGV/AMR can complete route and process changes by changing procedures.

High fault tolerance

AGV/AMR has the function of mixed-line transportation

Fast fault recovery When AGV/AMR fails, they can

be restored manually or automatically.

Economic benefits Reduce manpower input 20% Improve production turnover efficiency 20% Investment recovery cycle 1.5-2 Years



Solution

advantage

































# **NEW ENERGY PHOTOVOLTAIC**

# • • Requirement points

With the global fossil energy (oil, coal) increasingly close to exhaustion, climate warming ecological environment, countries around the world on the use of clean energy and carbon emission standards under strict requirements, photovoltaic power generation will become an important channel of energy output. In recent years, the application and development of photovoltaic energy storage technology is advocated vigorously by our country, and the industrial scale is expanded constantly. No matter in core technology, product manufacturing, equipment, or in market development, installation and service, it has a certain industrial chain with independent intellectual property rights, some of which have reached the international leading level. As an essential link in intelligent logistics, mobile robots are widely used in the photovoltaic industry, which greatly reduces the labor cost of logistics transportation and promotes the development of intelligent logistics.

#### Industry trends

(0)1

The mobile robot can realize the intelligent transportation of the photovoltaic industry's materials automatically on/off the line and in the middle of the transfer, and realize the unmanned automatic transportation;

M9


Intelligent transportation also has systematic management, data traceability, improve management level; (1)3}

By means of multi-system connection and integration, it can solve the problems of accuracy and efficiency of material transportation in each production line.















# **AUTOMOBILE & AUTO PARTS**

# • Requirement points

Overview

Under the background of electric and intelligent automobile, domestic automobile manufacturers have begun to carry out transformation and the background of electric and intelligent automobile.and upgrading of flexibility, agility, intelligence and information technology. As a standard configuration to achieve flexible manufacturing $and\ flexible\ assembly, mobile\ robots\ play\ an\ important\ role\ in\ the\ automobile\ and\ parts\ industry,\ helping\ the\ industry\ logistics\ upgrade\ from$ automation to intellectualization.

#### Industry trends

The production process of automobile industry is fixed, with high degree of standardization and automation, and intelligent transformation is convenient

The automotive industry has more than 10 years of experience in the use of mobile robots, and AGV/AMR has become a standard equipment

The overall production capacity of the automobile industry is high, and the demand for industrial mobile robots is large



Improve the automation and flexibility of entire automobile manufactures and improve per capita efficiency





area to take material











# Smart logistics solution

#### Improve production efficiency Improve the degree of automation

advantage automatically and efficiently fulfill capacity requirements

realize intelligent logistics and flexible manufacturing to meet the needs of personalized customization.

#### Reduce labor intensity

automatically send heavy materials to work stations

#### Economic 20% benefits

Optimize and reduce stock preparation and replenishment employees by more than

CRMS+CDSS+CASS

Solution composition

#### 100%

The accuracy rate of outbound shipments can be improved to

#### 100%

Timely rate for supply of parts to the production line can reach to

#### 20%

Reduce the area of warehouse management by more than















assembly parts sorting and preparation



## Partenr 🛇



















# FLAT PANEL DISPLAY INDUSTRY

# Requirement points

Industry Overview

The increasing consumer market stimulates the domestic flat panel display industry to develop towards the direction of large screen size  $and\ diversified\ functions. The\ panel\ design\ is\ diverse,\ the\ process\ is\ complex,\ the\ cross-line\ production\ switch\ is\ frequent,\ and\ the\ flexible$ production of enterprises requires the production line data information flow to be higher and higher. AGV/AMR gives the answer to intelligent production and transportation, enabling flat panel display enterprises to provide intelligent logistics comprehensive solutions and transportation and

Industry trends

Panel sizes are different. Micro LED and Mini LED have mainstream trend.

Different needs of vehicle, wearable, home appliances and industrial applications are the trend of personalized customization.

The process of different products is different, and cross-line production is frequently switched. Flexible production has become the general trend.

The types of raw materials are increasingly complex, and the requirements for fine management of warehousing and logistics are increasingly high.

Increasing labor more difficult





transport to the warehouse







Real-time data monitoring

the status of material information can be reported in real time to ensure the integrity of advantage the data chain and form a closed data loop.

Flexible process connection

cutting machine quickly, making production scheduling more flexible, to meet the diversified production mode.

Reduce labor cost

reduce material damage in the handling process, thus achieving cost reduction and efficiency increase

Economic benefits

Solution

Reduce the operating costs by

materials in the handling process
































Partenr ©

BOE京东方







INNOLUX







# 3C AND SEMICONDUCTOR INDUSTRY

# • Requirement points

With the development of "individual media", the extension of online services, and the trend of personalized and private consumption have continuously upgraded the demand for 3C products in China. Manufacturers in all aspects of the 3C field have an urgent demand for automatic transformation, and flexible assembly lines and intelligent three-dimensional warehouses have entered a stage of rapid development. The huge annual output value and volume of 3C electronics industry provide a huge market capacity for mobile robots; The contradiction between a large number of labor needs and recruitment difficulties promotes the intelligent upgrading of the whole industry.

#### Industry trends

(I)

3C electronics needs flexible logistics system to realize material transfer between multiple processes, while AGV/AMR can be adjusted timely with the change of production process flow.

#### M9

The low cost and high efficiency of mobile robots can relieve the recruitment pressure caused by the increasing shortage of human


#### 03

Real-time collection and reporting of production process data to solve the problems of precision and efficiency of material transportation in each production










#### Smart logistics solution Flexible transportation High work efficiency High safety dependence $advantage \quad {}^{AGV/AMR\,can\,complete\,route\,and\,process}$ 24H uninterrupted work all day to meet the AGV/AMR carrier implements wholedemand of production capacity changes by changing procedures process control with low error rate Improve the efficiency of picking and distribution in warehouse, and Economic Save labor force of factory benefits logistics by Solution composition CRMS+CDSS+CWMS





# LOGISTICS AND CIRCULATION INDUSTRY

# Requirement points

Industry

 $In \, recent \, years, with \, the \, support \, of \, national \, policies, \, logistics, \, cold \, chain \, fresh \, distribution \, and \, e-commerce \, logistics \, are \, developing$ rapidly towards intelligent logistics, and the industry is placing more emphasis on operational efficiency and benefit. As an essential part of  $in telligent \, logistics, mobile \, robots \, are \, widely \, used \, in \, the \, logistics \, industry, \, which \, greatly \, reduces \, the \, labor \, cost \, of \, the \, logistics \, circulation \, in the \, logistics \, circulation \, in the \, logistics \, circulation \, logistics \, circula$ Overview industry and promotes the development of intelligent logistics.

#### Industry trends

Logistics robots provide intelligent and To meet the industry demand for unmanned transportation from products to materials, such as automatic on-line, automatic offline, and intermediate transfer, and solve the problem of low efficiency in 

cost reduction and efficiency increase, fully intelligent management can improve the management level and effectively avoid a series of factors such as

Large volume of business


product data management

requires data tracking:

traceability

The industry has high requirements for storage capacity. Mobile robots can meet the requirements of narrow tunnels and high shelves for compact storage layout, saving space costs.







ase wideo









## SERVICE CONCEPT



**SPECIALTY** 



**EFFICIENT** 



**HIGH QUALITY** 





## **Product consulting**

General/custom product function and selection recommendation

#### **Product planning**

Site investigation, scheme design, process planning.

#### System design

Control system design and development

## Sale

#### Product customization

Production and development of customized products

#### System development

Software development deployment

#### Installation

Software and hardware Deployment

#### After sales

#### Training

Product/system maintenance training

#### Operating services

Mobile robot management and maintenance

#### Maintenance service

After-sales support, regular inspection, 7\*24 hours customer service consultation

#### **SERVICE PROCESS**



**⟨¹**⟩





Consultation

Scenario Design

Sign contract

Design and develop



Service Provider



**Technical Support** 



ODM Order



website



WeChat





Official Account



video account





Tiktok



Toutiao



